

IMAX Private Theatre Platinum[™]

IMAX Private Theatre Platinum™ draws on IMAX's legacy of excellence and groundbreaking technologies in delivering the highest audio and visual standards to create the ultimate immersive entertainment solution for private spaces. It brings the same philosophy used in the world's leading IMAX® movie theatres to your home, for the optimum delivery of the best entertainment experiences across the media spectrum.

- · Dual 4K 2D/3D laser projectors
- Advanced image super enhancer
- · immersive IMAX® curved screen and movable frame
- Proprietary IMAX® sound system
- · Quality equalizer and power amplifier
- HD multi-media content server and player (supporting HD television, Blu-ray™, DVD, CD, gaming and karaoke)
- · Touch-screen control pad with dedicated control system
- · x3 pairs of professional 3D glasses
- * Space Requirement: ~80 -~180 sq.m



Contact us:

IMAX FZE, 14303 JAFZA Offices, PO Box 17366, Dubai, UAE IMAX Private Theatre $^{\mathsf{TM}}$, MENA

T: +9718818198

E: MENASales@imaxprivatetheatre.com

IMAX Private Theatre Platinum[™] System Specification

Video System	Projection system	Dual projectors
	Projector alignment	Automatic calibration
	Display resolution	4096 x 2160 (Native 4K)
	End to End 4K support	Yes
	2D brightness ¹	30fl-L
	3D brightness ¹	10fl-L per eye
	3D mode	Passive
	3D format	L/R separation, Frame packing, SBS, Top and Bottom
	3D/2D switch	Automatic 2D / 3D input detection and 3D filter on/off
	Native contrast (ON/OFF)	≥4000:1
	Throw ratio	1.35 - 2.30
	Lamp life ²	1500hrs - 3000hrs
	Pixel depth	12bit
	Constant brightness	Yes
	Playback (JPEG2000)	4K 2D:24P 2K 2D: 24/30/48/60P 2K 3D:24/30/48/60P
	Color gamut	DCI P3, Rec.709
	4K scaler	Yes
	I/P (Interlaced/Progressive) conversion	Yes
	Physical Blu-ray™ disc support	Yes
	Streaming video support	Yes
	DCI support	Yes

Note: 1. Brightness levels for individual products are determined by whether IMAX Private Theatre standard screen size is applied.

2. Lamp Life is determined by screen size.

	Screen aspect ratio	1.896:1
Screen	Screen material	Silver, Micro-perforated screen
33.33.1	Maximum screen size	430 inches diagonal (9.5m x 5m)
_	MUXIIII0III 3CI GGII 312G	430 menes diagonal (7.3m x 3m)
	HDMIinput	8 ways
Audio System	Dolby Digital Plus / Dolby TrueHD / Dolby	
	Surround / Dolby Atmos	Supported
	DTS ES / DTS 96 / 24 / DTS-HD Master / DTS X	Supported (only Blu-ray)
	PCM multi-channel	Supported
	HDCP2.2 compatibilities	Yes
	Preamplifier analog output type	XLR (Balance)
	Power amplifier output (front channel / per channel)	700W*3+300W
	Power amplifier output (surround channel / per channel)	350W
	Front channel loudspeaker response	40Hz - 20kHz (-3dB)
	Front channel loudspeaker sensitivity	95dB (1m/1W)
	Front channel loudspeaker dispersion pattern	80°Horizontal, 35°Vertical (1.5kHz/-6dB)
	Front channel loudspeaker MAX SPL (1m)	128dB continuous, 132dB peak
	Surround channel loudspeaker response	80Hz – 20kHz (-3dB)
	Surround channel loudspeaker sensitivity	92dB (1m/1W)
	Surround channel loudspeaker dispersion pattern	80°Horizontal, 50°Vertical (1.5kHz/-6dB)
	Surround channel loudspeaker MAX SPL (1m)	116dB continuous, 122dB peak
	Subwoofer response	18Hz (-3dB)
	Subwoofer sensitivity	102dB (1m/1W)
	Subwoofer MAX SPL (1 m 50Hz)	133dB continuous, 139dB peak
Control	Control PC	Industrial grade central control computer
Control	Control system	IMAX Private Theatre proprietary control system
System	Controller	Android Tablet
	Ul language	English
	System status remote monitoring (24H/7D)	Yes, working status monitoring of all the key equipment, including projector, speakers, central control server, etc.
Remote	Auto failure report	Yes
Monitoring	Remote diagnosis	Yes
and	SADA (speaker work status auto detect)	Yes
Support	Temperature & humidity monitoring	Yes
	, , , , , , , , , , , , , , , , , , ,	
Povyer	PDU	Included
Power System	UPS	Included
39316111	Power of the full system	12000VA
	Projectors	546mm * 633mm * 1118mm each
Equipment	L/R/C speakers	980mm * 480mm * 279mm each
Size	Surround speakers	409mm * 470mm * 201mm each
	Subwoofers	671mm * 1049mm * 300mm each

Recommended Room Size:

Room Size Range (Outer Shell)	80 - 180 sq.m
Room Ceiling Height	4 – 6 meters
Standard Screen Size	260 – 480 inches
Seating Capacity	20 – 60 standard IMAX Private Theatre seats

