

IMAX Private Theatre Palais™

IMAX Private Theatre Palais™ brings patented IMAX® technology and its immersive experience to medium-sized private theatres of between 5 and 20 seats. To ensure ongoing satisfaction, IMAX Private Theatre Palais™ benefit from a smart daily image calibration function and 24/7 system performance monitoring.

- Dual 4K 2D/3D projectors
 - Advanced image super enhancer
 - Immersive IMAX® curved screen and movable frame
 - Proprietary IMAX® sound system
 - Media server
 - Blu-ray™ player
 - Support for additional sources (DVD, CD, streaming, gaming, karaoke)
 - Touch-screen control pad with dedicated control system
 - 20 pairs (adults) + 5 pairs (kids) of professional 3D glasses
- * Space Requirement: ~480 - ~760 sq.ft



Contact us:

IMAX FZE, 14303 JAFZA Offices, PO Box 17366, Dubai, UAE

IMAX Private Theatre™, MENA

T: +971 881 8198

E: MENASales@imaxprivatetheatre.com

IMAX Private Theatre Palais™ System Specification

Video System	Projection system	Dual projectors
	Projector alignment	Automatic calibration, accuracy to 0.25 pixel level
	Display resolution	4096 x 2160 (Native 4K)
	End to End 4K support	Yes
	2D brightness ¹	30fl-L
	3D brightness ¹	6fl-L per eye
	3D mode	Passive
	3D format	L/R separation, frame packing, top and bottom
	3D/2D switch	Automatic 2D / 3D input detection and 3D filter on/off
	Native contrast (ON/OFF)	≥ 5000:1
	Throw ratio	1.27 - 2.73
	Lamp life ²	≥ 2000hrs
	HDMI input compatibility	HDMI2.0 & HDCP2.2. downward compatibility
	Pixel depth	12bit
	Constant brightness	Yes
	Maximum video format	4096 x 2160 @ 60P
	Video format support	4K (4096x2160) @24P/60P and other common formats, such as 4K (3840x2160) @24P/60P, 1080@50/60P, 1080@24P, 720@50/60P, 1080@50/60i, etc.
	Color gamut	DCI P3, Rec.709
	4K scaler	Yes
	I/P (Interlaced/Progressive) conversion	Yes
Physical Blu-ray™ disc support	Yes	
Streaming video support	Yes	
DCI support	No	

Note: 1. Brightness levels for individual products are determined by whether IMAX Private Theatre standard screen size is applied.

2. Lamp Life is determined by screen size.

The information in this Specification Sheet is of a preliminary nature and is subject to change based on continuing development work being performed by TCL-IMAX.

Screen	Screen aspect ratio	1.896:1
	Screen material	Silver, Micro-perforated screen
	Maximum screen size	240 inches
Audio System	HDMI input	8 ways
	Dolby Digital Plus / Dolby TrueHD / Dolby Surround / Dolby Atmos	Supported
	DTS ES / DTS 96 / 24 / DTS-HD Master / DTS X	Supported
	PCM multi-channel	Supported
	HDCP2.2 compatibilities	Yes
	Preamplifier analog output type	XLR (Balance)
	Power amplifier output (per channel)	360W/8Ω, 700W/4Ω, 1000W/8Ω (Bridge)
	Front channel loudspeaker response	40Hz – 20kHz (-3dB)
	Front channel loudspeaker sensitivity	96dB (1m/1W)
	Front channel loudspeaker dispersion pattern	80°Horizontal, 50°Vertical (1.5kHz/-6dB)
	Front channel loudspeaker MAX SPL (1m)	122dB continuous, 126dB peak
	Surround channel loudspeaker response	80Hz – 20kHz (-3dB)
	Surround channel loudspeaker sensitivity	92dB (1m/1W)
	Surround channel loudspeaker dispersion pattern	80°Horizontal, 50°Vertical (1.5kHz/-6dB)
	Surround channel loudspeaker MAX SPL (1m)	116dB continuous, 122dB peak
	Subwoofer response	18Hz (-3dB)
Subwoofer sensitivity	102dB (1m/1W)	
Subwoofer MAX SPL (1m 50Hz)	132dB continuous, 138dB peak	
Control System	Control PC	Industrial grade central control computer
	Control system	IMAX Private Theatre™ proprietary control system
	Controller	Android Tablet
	UI language	English
Remote Monitoring and Support	System status remote monitoring (24H/7D)	Yes, working status monitoring of all the key equipment, including projector, speakers, central control server, etc.
	Auto failure report	Yes
	Remote diagnosis	Yes
	SADA (speaker work status auto detect)	Yes
Temperature & Humidity monitoring	Yes	
Power System	PDU	Included
	UPS	Included
	Power of the full system	3000VA
Equipment Size	Projectors	645 mm * 520 mm * 220 mm each
	L/R/Cspeakers	480 mm * 570 mm * 280 mm each
	Surround speakers	470 mm * 410 mm * 200 mm each
	Subwoofers	1050 mm * 670 mm * 300 mm each
	A/V rack	600 mm * 800 mm * 1687 mm each

Recommended Room Size:

Room Ceiling Height	2.4 – 3.8 meters
Screen Size	165 – 240 inches (include 5 standard size: XS 165/ S 180/ M 200/ L 220/ XL 240)
Seating Capacity	5 – 20 standard IMAX Private Theatre seats

